

Technical Data

Design :	Pneumatic double-piston quarter turn actuator
Design features :	Rack-and-pinion system, piston guide via guide rods
Angle of rotation :	0°-135°
Air pressure supply :	mind. 2 bar, max. 8 bar
Operating medium :	Dry and filtered compressed air
Ambient temperature :	-25°C to +80°C
Mounting position :	any
Resistance to corrosion :	Industrial atmosphere
Lubrication :	Life time lubrication with grease ISO 51825-K2K-30
Seals :	NBR-O-Rings, 70 Shore
Coatings :	Housing anodized and colour sealed End caps - CED cathodic electrodeposition
Maintenance and inspection :	AMG actuators are free of maintenance within the life time. Provided that: <ul style="list-style-type: none"> • the actuator is properly mounted • the operating medium used is clean and non-aggressive • the actuator is operated under normal ambient conditions • the actuator is used in compliance with the intended use (see assembly and maintenance manual)
Applied standard:	DIN EN ISO 5211, DIN EN 15714-3, VDI / VDE 3845, DIN 79
Options:	Adjustable inner / outer travel stops up to +/- 5° via travel-stop-module (TSM) Ambient temperature up to +100°C Ambient temperature down to -40°C Sealing elements made of FKM (viton) or alternatively fluorosilicone Tailor made mounting kits and dimensioning acc. To customer requirements Variable cycle times (fast / slow) Variable sens of rotation (clockwise / counterclockwise) Coating options: Hard-Coat, chemical nickelplating, plastic coating, special lacquer




SAD - 135°

DOUBLE-PISTON QUARTER TURN ACTUATORS

TYPE BR16 SAD 135°

Size	43
Weight [kg]	67,9
Stroke volume [dm³]	31,3
Operating times [sec.] ¹⁾	
OPEN	5,0
CLOSE	5,0

1) operating times at 4,5 bar air pressure supply without load (standard values)



Type	air torque Ma [Nm] at operating pressure pe [bar]													
	2 bar		2,5 bar		3 bar		3,5 bar		4 bar		4,5 bar		5 bar	
	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX
SAD 43	715	926	1136	1340	1548	1761	1967	2175	2385	2598	2798	2998	3197	

Design	SAD
Size	43
A (double-acting)	604
A1 (single-acting)	-
B	288
C	296
D	20
E	146
F	144
G	84
H	108
K	150
Ø L#	106
J	84
Ø M#	258
N	80
O	12
Ø P#	63
SW	30
Connection ISO 5211	F16
Ø d2#	130
h4	3
Ø d3#	165
4x d4xh3#	4x M20x32
Ø d5#	-
l3#	50
s	46
4x d6xh5	-
8x d7xh6	8x M16x24
Y	170
Z	96
W1	220
X1	116
G1	-